



- Extra Life and Protection
- Special Applications

# Shell Omala S4 GXV 680

## Advanced Synthetic Industrial Gear Oil

Shell Omala S4 GXV 680 is an advanced synthetic heavy duty industrial gear oil, approved by Flender, offering outstanding lubrication performance under severe operating conditions, including reduced friction, long service life, high resistance to micro-pitting for optimal gear protection and superb compatibility with seals.

### DESIGNED TO MEET CHALLENGES

#### Performance, Features & Benefits

- **Long oil life - maintenance saving**

Shell Omala S4 GXV 680 is formulated using an advanced additive system in combination with specially selected synthetic base fluids to provide outstanding resistance to breakdown over long duration and/or high temperature operation.

Shell Omala S4 GXV 680 can operate successfully at bulk temperatures up to 120°C. Shell Omala S4 GXV 680 offers the potential to significantly extend service intervals compared to conventional industrial gear oils.

- **Excellent wear and corrosion protection**

Shell Omala S4 GXV 680 is formulated to have excellent load carrying capacity and micro-pitting performance providing long component life even under shock loading conditions. These features provide benefits over mineral oil-based products in terms of gear and bearing component life.

Shell Omala S4 GXV 680 also has excellent corrosion protection, even in the presence of contamination by water and solids.

- **Maintaining system efficiency**

Shell Omala S4 GXV 680 can help maintain or enhance the efficiency of industrial gear systems through improved low temperature performance and lower friction in comparison to mineral oil-based products. This provides better lubrication at low start-up temperatures.

#### Main Applications



- **Gear motor systems and other inaccessible installations**

Shell Omala S4 GXV 680 is particularly recommended for certain systems where extra long life is required, maintenance is infrequent or systems are inaccessible.

- **Excellent compatibility with seals, paints and sealants**

Recommended for industrial reduction gear systems using a wide range of seals, including nitrile rubber and fluoro-elastomers. Meets the demanding requirements of Flender gearboxes and gear motors.

- **Enclosed industrial gear systems**

Recommended for industrial reduction gear systems operating under severe operating conditions, such as high load, very low or elevated temperatures and wide temperature variations.

- **Other applications**

Shell Omala S4 GXV 680 is suitable for lubrication of bearings and other components in circulating and splash-lubricated systems.

For highly loaded worm drives the Shell Omala "W" series oils are recommended. For automotive hypoid gears, the appropriate Shell Spirax Oil should be used.

## Specifications, Approvals & Recommendations

- ISO 12925-1 Type CKD
- ANSI/AGMA 9005-F16
- Flender – approved according to Flender T 7300 Omala S4 GXV ISO 150 – 680 are approved by Flender for use in Flender gearboxes and gear motors.
- DIN 51517-3 (CLP)

- China National Standard GB 5903-2011 CKD
- AIST (US Steel) Req. No. 224

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

## Typical Physical Characteristics

Properties			Method	Shell Omala S4 GXV 680
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ASTM D445	680
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ASTM D445	74
Viscosity Index			ASTM D2270	191
Flash Point (COC)		°C minimum	ASTM D92	240
Pour Point		°C	ASTM D97	-42
Density	@15°C	kg/m <sup>3</sup>	ASTM D4052	868
Four Ball EP Weld load		kg minimum	ASTM D2783	250
FZG Load Carrying Test A/8.3/90		failure load stage	ISO 14635-1	>12
FZG Load Carrying Test A/8.3/90 Modified		failure load stage	ISO 14635-1 Modified	>14

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### • Health and Safety

Omala S4 GXV 680 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### • Change over procedure

Omala S4 GXV 680 is based on synthesized hydrocarbon fluids and is compatible with petroleum mineral oil-based industrial gear lubricants - no special change-over procedure is necessary. However, to achieve the complete benefit of Omala S4 GXV 680, it should not be mixed with other oils.

It is also advisable to ensure that oil systems are clean and free from contamination.

### • Advice

Advice on applications not covered here may be obtained from your Shell representative.

