



Formerly Known As: Shell Corena AP

Shell Corena S4 P 68

- Extra Long Life
- Improved Efficiency
- Severe Applications

Advanced Synthetic Reciprocating (Piston) Air Compressor Oil

Shell Corena S4 P is an advanced synthetic air compressor oil incorporating synthetic ester base fluids and a unique high performance additive system. It is designed to deliver the highest performance lubrication for high pressure reciprocating compressors running in excess of 220°C discharge temperatures at elevated pressures.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Long oil life – Maintenance saving**

Shell Corena S4 P is designed to provide safe, reliable and effective lubrication for extended service periods where mineral compressor lubricants are unsatisfactory.

Shell Corena S4 P helps ensure continued high performance of the compressor over long periods and reduces maintenance costs and shutdowns.

Shell Corena S4 P can extend the normal valve maintenance period from typically up to 1000 hours of operation using conventional mineral oils, to 2000 to 4000 hours depending on operating conditions.

- **Outstanding wear protection**

Shell Corena S4 P helps provide exceptional protection of internal metal surfaces from corrosion and wear to help prolong the life of critical parts such as bearings and gears.

- **Maintaining system efficiency**

Shell Corena S4 P helps prevent the formation of carbon deposits and lacquer on valves and piston crowns at high working temperatures and pressures.

Shell Corena S4 P has excellent water separation to help prevent accelerated corrosion and facilitating easy draining of condensate.

- **Enhanced air line safety**

In discharge air lines, the combination of rust particles, dispersed in carbonaceous deposits, coupled with heat from recently compressed air, can cause a reaction leading to the possibility of fires and explosion. Shell Corena S4 P helps to minimise the likelihood of this danger.

Main Applications



- **Reciprocating air compressors**

Shell Corena S4 P is suitable for all industrial reciprocating air compressors, in particular those operating under severe conditions of air discharge temperatures in excess of 220°C with continuous high delivery pressures.

- **Breathing air compressors**

Shell Corena S4 P may be used in breathing air compressors, provided subsidiary clean-up apparatus is used to ensure that the air produced is fit for breathing.

Specifications, Approvals & Recommendations

- BS EN 12021
- DIN 51506 VDL, ISO/DP 6521-L-DAB - medium duty
- ISO 6743-3 2003 DAB - Serve duty

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Compatibility & Miscibility

- **Miscibility**

Shell Corena S4 P oils are fully miscible with mineral oils, although dilution with mineral lubricants will markedly reduce their performance.

- **Seal Compatibility**

Shell Corena S4 P, in common with other ester-based lubricants, is not compatible with all seal materials. Some older compressors may need to have the seals changed before they can be run on the new grades.

- **Compatibility Guide : Acceptable**

High nitrile content (SEB5)
>36% acrylonitrile

- **Compatibility Guide : Majority Acceptable**

Medium nitrile content (SE70)
30 - 36% acrylonitrile

- **Compatibility Guide : Not recommended**

Low nitrile content
<30% acrylonitrile

Typical physical Characteristics

Properties			Method	Shell Corena S4 P 68
ISO Viscosity Grade			ISO 3448	68
Performance Standard			DIN 51506	VDL 68
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	68
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	8.5
density	@15°C	kg/m ³	ASTM D 1298	990
Flash Point		°C	ASTM D 92 (COC)	250
Pour Point		°C	ASTM D 97	-51
Sulphated Ash		%m	DIN 51575	<0.02
Rust Prevention - Distilled Water	24 hrs	Pass	ASTM D 665A	Pass
Copper Corrosion	(100°C/3hr	°C	ASTM D130	1b
Water Separability	@54°C	min	ASTM D1401	30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Corena S4 P Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.

Viscosity - Temperature Diagram for Shell Corena S4 P

