



Shell Rimula R3+ 30

Heavy Duty Diesel Engine Oil

Shell Rimula R3 oils adapts to your driving needs to provide extra protection and keep pistons and other engine parts clean. It provides protection against wear for long engine life and protection against deposits for efficient engine performance.

- Extra Performance



Performance, Features & Benefits

- **Equipment manufacturer acceptance**
Shell Rimula R3 monogrades are approved for use in a variety of engine applications by leading OEMs.
- **High standard of piston cleanliness**
The high thermal stability and oil oxidation resistance provide a high standard of piston cleanliness.
- **Low engine wear and long component life**
Overall engine cleanliness contributes to low engine wear, long component life, maintenance of power output, more operational stability and lower servicing costs.

- **Construction industry application**

Engine oil technology is sometimes specified for use in the transmission and hydraulic applications. Shell Rimula R3 monogrades offer premium performance and protection for these applications.

- **Stationary equipment**

Shell Rimula R3 monogrades are suitable for certain stationary equipment, such as pumps, that run continuously under steady state conditions.

- Shell Rimula R3+ 30 is suitable for use with biodiesel per the OEM recommended oil drain intervals

Main Applications



- **Dedicated diesel engine oil performance**
Shell Rimula R3 monogrades have been formulated to provide robust engine performance in a variety of off-highway applications or older on-highway diesel vehicles.

Specifications, Approvals & Recommendations

- MAN 270
- MB Approval 228.0
- MTU Category 1
- API CF

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Compatibility & Miscibility

- Shell Rimula R3 oils should not be used in Detroit Diesel two-stroke engines. An SAE 40 oil meeting the API CF-II Specification and having a sulphated ash content of less than 1% should be used.

Typical physical Characteristics

Properties			Method	Shell Rimula R3+ 30
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	93
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	11
Viscosity Index			ASTM D2270	103
Density	@15°C	kg/L	ASTM D4052	0.89
Flash Point (COC)		°C	ASTM D92	242
Pour Point		°C	ASTM D97	-18

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Rimula R3+ is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell Representative.

