



Shell Rimula *Light Duty LD3 Multi 15W-40*

- For Diesel Engines

Specially Designed Engine Oil for Light Commercial Vehicles

Provides reliable protection for a wide range of light duty engines and operating conditions



Performance, Features & Benefits

• Engine cleanliness

The high thermal stability and oil oxidation resistance provide a high standard of protection against piston deposits. Engine cleanliness is further enhanced through use of high performance dispersants to control sludge and deposits in other parts of the engine.

• Low engine wear

The combination of active anti-wear additives and good engine cleanliness controls engine wear, gives long engine life, maintains engine power and efficiency and lowers servicing costs.

• Specially designed for light commercial vehicles

Formulated to provide reliable engine protection in urban/city driving conditions such as Stop-Start and variable load applications. The additive technology helps protect the engine from soot related deposits which can be caused by high idle applications.

- For more heavy duty applications kindly use the Rimula R3/R4 range of products.

Specifications, Approvals & Recommendations

- API CH-4
- For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Main Applications



Typical Physical Characteristics

Properties			Method	Shell Rimula Light Duty LD3 Multi 15W-40
Kinematic Viscosity	@40°C	cSt	ASTM D445	105.1
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.3
Viscosity Index			ASTM D2270	139
Dynamic Viscosity	@-20°C	mPas	ASTM D5293	6600
Density	@15°C	kg/l	ASTM D4052	0.886
Flash Point (COC)		°C	ASTM D92	230
Pour Point		°C	ASTM D97	-36

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Rimula Light Duty LD3 Multi 15W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from www.epc.shell.com

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.

