

PENNZOIL® SAE 10W-30 MOTOR OIL

TECHNICAL DATA SHEET



Pennzoil® Motor Oil with Active Cleansing Technology. Helps prevent dirt and contaminants from turning into performance robbing deposits. Because at Pennzoil® we know, a cleaner engine is better protected and responsive. It meets or exceeds the engine protection required by ILSAC GF-6A, and is specially formulated to provide proven wear protection.

PERFORMANCE, FEATURES & BENEFITS

- Pennzoil® SAE 10W-30 motor oil with Active Cleansing Technology meets the toughest industry standards
- Keeps engine clean and responsive
- Provides proven wear protection
- Suitable for all car, SUV, light van and truck gasoline engines; under all driving conditions

MAIN APPLICATIONS

Pennzoil® SAE 10W-30 is recommended for use in all vehicles requiring the use of SAE 10W-30 viscosity grade engine oils under all driving conditions.

Pennzoil® SAE 10W-30 Motor Oil can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Meets or exceeds the following OEM requirements:

- Chrysler MS-6395

Exceeds the requirements of the following industry specifications:

- API SP
- API SP-Resource Conserving and all previous Categories
- ILSAC GF-6A and all previous ILSAC Standards

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

To find the right Pennzoil® product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

TYPICAL PHYSICAL CHARACTERISTICS

| Properties | Method | Pennzoil® SAE 10W-30 Motor Oil |
|------------------|-------------------|--------------------------------|
| Viscosity Grade | SAE J300 | 10W-30 |
| Service Category | | SP-RC |
| ILSAC | | GF-6A |
| ACEA | | N/A |
| Density @15°C | kg/m ³ | 869.9 |
| Flash Point | °C | 212 |
| Flash Point | °C | 236 |

© SOPUS Products 2022. All rights reserved.

PENNZOIL® SAE 10W-30 MOTOR OIL

| Properties | | | Method | Pennzoil® SAE 10W-30 Motor Oil |
|---------------------|--------|-----|------------|--------------------------------|
| Pour Point | | °C | ASTM D97 | -42 |
| Kinematic Viscosity | @100°C | cSt | ASTM D445 | 10.73 |
| Kinematic Viscosity | @40°C | cSt | ASTM D445 | 71.91 |
| Viscosity Index | | | ASTM D2270 | 138 |
| CCS Viscosity | @-25°C | cP | ASTM D5293 | 6 200 |
| MRV Viscosity | @-30°C | cP | ASTM D4684 | 23 000 |

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

Pennzoil® SAE 10W-30 Motor Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or local technical helpdesk.