



# Shell Helix *HYBRID 0W-20*

## Fully Synthetic Passenger Car Motor Oil

Shell Helix HYBRID is specially designed for modern fuel efficient gasoline engines built in hybrid-electric vehicles.

### Proud Drivers Choose Shell Helix

#### Main Applications

- Shell Helix HYBRID is specially designed for modern fuel efficient gasoline engines found in hybrid-electric vehicles. It is suitable for most hybrid vehicles from Japanese, American and other vehicle manufacturers.

#### Specifications, Approvals & Recommendations

- API SP
- ILSAC GF-6A

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <https://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

#### Typical Physical Characteristics

Properties			Method	Shell Helix HYBRID 0W-20
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.59
Kinematic Viscosity	@40°C	cSt	ASTM D445	46.75
Viscosity Index			ASTM D2270	164
	@15°C	Kg/m <sup>3</sup>	ASTM D4052	836.1
Flash Point		°C	ASTM D92	243
Pour Point		°C	ASTM D97	-54

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

#### Health, Safety & Environment

##### • Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

##### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.