



Formerly Known As: Shell Spirax AX Plus 80W-90

Shell Spirax S3 AD 80W-90

High Performance, API GL-5 Axle oil for Mercedes-Benz, MAN and ZF applications

Shell Spirax S3 AD 80W-90 is an extreme-pressure lubricant containing multi-functional additives which impart good anti-wear, oxidation stability and anti-rust characteristics. It is suitable for gear applications presenting load-speed conditions of extreme severity, such as medium and low speed spur or helical gear units, spiral-bevel and hypoid axle units as well as extended drain capabilities.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Longer oil drain capability**

Higher reserves of additives ensure long-term protection of gears. Longer oil life, as a result of higher oxidation stability and lower running temperatures, also leads to extended oil drain intervals.

- **Longer gear life**

Clear improvements in protection against wear helps prevent premature failure. High oxidation resistance also prevents damaging deposit formation in axles.

- **Comprehensive components**

Specially selected additives impart good anti-wear especially at high operating temperature conditions, oxidation stability, anti-rust characteristics and yellow metal compatibility.

- **Axles and differentials**

Heavy duty SAE 80W-90 axle oil blended to meet the stringent requirements of Mercedes-Benz, MAN and ZF for extended drain.

Specifications, Approvals & Recommendations

- DTFR 12B110
- MAN : 342 Type M3
- ZF TE-ML : 05A, 12L, 12M, 16B, 17B, 19B, 21A
- API Service Classification : GL-5, MT-1
- SAE J 2360 : Meets requirements

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



Typical physical characteristics

Properties			Method	Shell Spirax S3 AD 80W-90
SAE Viscosity Grade				80W-90
Kinematic Viscosity	@40°C	mm ² /s	ISO 3104	137
Kinematic Viscosity	@100°C	mm ² /s	ISO 3104	14.4
Viscosity Index			ISO 2909	104
Density	@15°C	kg/m ³	ISO 12185	899
Flash Point (COG)			ISO 2592	204
Pour Point			ISO 3016	-33

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Spirax S3 AD 80W-90 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your shell representative.