



# Shell Helix *Ultra Professional* AP-L 5W-30

*Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements*

Designed to meet the demanding requirements of particular high-performance engines, including Peugeot, Citroen, and those requiring ACEA C2.

Proud Drivers Choose Shell Helix

## Main Applications

- Shell Helix Ultra Professional AP-L 5W-30 for diesel engines meets the technically challenging Peugeot B71 2290 in-house specifications (for Euro 5 diesel and older).
- It is formulated specifically for use in modern Peugeot diesel engines using diesel particulate filter technology.
- For Euro 6 diesel engines fitted with SCR system (Adblue) Helix Ultra AP-L 0W-30 can be used. Please consult owners manual.

## Specifications, Approvals & Recommendations

- API SN
- ACEA C2
- PSA B71 2290 (meets requirements for Euro 5 diesel and older)

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

## Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AP-L 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	10.2
Kinematic Viscosity	@40°C	cSt	ASTM D445	59.59
Viscosity Index			ASTM D2270	162
MRV	@-35°C	cP	ASTM D4684	11 800
Density	@15°C	Kg/m <sup>3</sup>	ASTM D4052	843.7
Flash Point		°C	ASTM D92	233
Pour Point		°C	ASTM D97	-48

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### • Health and Safety

Shell Helix Ultra Professional AP-L 5W-30 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com/>

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.