



Formerly Known As: Shell Transaxle Oil 75W-90

Shell Spirax S5 ATE 75W-90

Premium performance, synthetic technology, GL-4/5 Spirax S5 ATE 75W-90 for sports cars

Shell Spirax S5 ATE 75W-90 is particularly designed to fulfil the highest requirements of extremely loaded passenger car drive train systems.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Outstanding gear protection and synchronmesh performance**
Careful choice of base oils combined with new additive technologies achieve highest level of performance in the particular “transaxle” transmission type designs, where gear protection and high and stable synchronmesh compatibility are required.
- **Longer equipment life**
High shear stable formulation and durable extreme pressure (EP) performance allow an excellent protection against gear wear and pitting, preventing premature failure, and ensure longer component and lubricant life. Outstanding thermal and oxidation resistance also prevents damage to seals from deposit formation.
- **Improved drive train efficiency**
Shell Spirax S5 ATE 75W-90 reduces friction losses in the drive train improving therefore efficiency and performance. As synthetic lubricant it ensures optimal lubrication at low and high temperature.
- **Environmentally friendly**
Excellent seal compatibility guarantees protection against leaks. Low-chlorine formulation and extended drain interval capability ensures less environmental impact.
- **Recognised and used by leading sports car manufacturers**
Shell Spirax S5 ATE 75W-90 benefits have been recognised by a number of leading sport car manufacturers who are using it as initial and service fill gear oil.
- **Part of the Shell synthetic lubricants team**
Use in conjunction with other Shell synthetic lubricants for maximum benefit.

Main Applications



- **Transaxle transmissions**
Heavily loaded “transaxle” transmission where hypoid axle and gearbox are in the same housing and lubricated by the same product. Particularly in sport passenger car drive train systems.
- **Automotive transmissions**
Heavily loaded axle drives, synchronised and non-synchronised gearboxes.

Specifications, Approvals & Recommendations

- Ferrari
- Getrag
- MB 236.26
- API Service Classification : GL-4, GL-5, MT-1

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

| Properties | | | Method | Shell Spirax S5 ATE 75W-90 |
|---------------------|--------|--------------------|-----------|----------------------------|
| SAE Viscosity Grade | | | SAE J 306 | 75W-90 |
| Kinematic Viscosity | @40°C | mm ² /s | ISO 3104 | 81 |
| Kinematic Viscosity | @100°C | mm ² /s | ISO 3104 | 14.9 |
| Viscosity Index | | | ISO 2909 | 194 |
| Dynamic Viscosity | @-40°C | mPa s | ISO 9262 | 35 000 |
| Density | @15°C | kg/m ³ | ISO 12185 | 879 |
| Flash Point (COC) | | | °C | 205 |
| Pour Point | | | °C | -45 |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Spirax S5 ATE 75W-90 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <https://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.