Shell **Helix** *Ultra Professional AJ-L 0W-20*

WITH Shell PUREPLUS TECHNOLOGY

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

Designed to meet the demanding requirements of particular high-performance gasoline engines from Jaguar Land Rover and those requiring API SN. It helps to reduce engine friction to provide enhanced fuel economy.

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix Ultra Professional AJ-L is approved against the technically challenging Jaguar-Land Rover gasoline engine oil specification STJLR 51.5122, and diesel and gasoline Ford engine oil specification WSS-M2C952-A1. It is formulated specifically for use in Jaguar-Land Rover and Ford vehicles calling for these specifications which combines ACEA engine tests with special JLR in-house testing and evaluation. Also, suitable where API SN performance is required.

Specifications, Approvals & Recommendations

- API SN
- ACEA C5
- Jaguar Land Rover STJLR 51.5122
- Ford WSS-M2C952-A1

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AJ-L 0W-20
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.20
Kinematic Viscosity	@40°C	cSt	ASTM D445	41.90
Viscosity Index			ASTM D2270	174
MRV	@-40°C	cP	ASTM D4684	11 200
Density	@15°C	kg/m^3	ASTM D4052	832.7
Flash Point		°C	ASTM D92	232
Pour Point		°C	ASTM D97	-60

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

  This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

  Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

  Guidance on health and safety is available on the appropriate Safety Data Sheet, which can be obtained from https://epc.shell.com

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.