



WITH
Shell
PUREPLUS
TECHNOLOGY

Shell Helix *POWER 0W-40*

Fully Synthetic Passenger Car Motor Oil

Shell Helix Power is expertly engineered for ultimate engine power and performance in your car.

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix POWER is suitable for a wide range of modern gasoline and diesel passenger cars (without diesel particulate filters). It is particularly suitable for high power and performance vehicles.

Specifications, Approvals & Recommendations

- API SP
- ACEA A3/B3, A3/B4

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at:
<http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix POWER 0W-40
Kinematic Viscosity	@100°C	cSt	ASTM D445	13.1
Kinematic Viscosity	@40°C	cSt	ASTM D445	74.2
Viscosity Index			ASTM D2270	180
MRV Viscosity	@-40°C	cP	ASTM D4684	28 500
Density	@15°C	kg/m ³	ASTM D4052	839
Flash Point		°C	ASTM D92	230
Pour Point		°C	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.