



Shell Gadus S4 OGXK

- Superior Wear Resistance
- Long Life
- Aluminum Complex

Premium Open Gear and Wire Rope Grease

Shell Gadus S4 OGXK is primarily designed for use in heavily loaded applications, and operations under arctic conditions, in mining equipment, shovels, draglines and excavators in open cut operations. Shell Gadus S4 OGXK is based on Aluminium Complex soap thickener and high viscosity semi-synthetic base oil containing enhanced extreme pressure and antiwear chemistry. Diluent is used to ensure low-temperature pumpability.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Excellent load carrying capacity under severe operation conditions**
Grease contains selected components to ensure excellent resistance to shock and permanently heavy loads.
- **Very high mechanical and thermal stability**
Grease thickener structure is designed to resist mechanical stress and high temperature.
- **Withstanding severe operation conditions**
Like dust and dirt contamination, water, and changes in temperature. Shell Gadus S4 OGXK is optimized for use in ambient temperatures between - 50°C to +10°C.
- **Maintain adhesive characteristic over time**
Thanks to advanced polymer technology ensuring durable protection. Forms a dark coating on metal surfaces that is adhesive and highly water resistant.
- **Low Friction**
Selected components ensure low friction characteristics, lower energy consumption and wear reduction.
- **Environmental compliance**
Shell Gadus S4 OGXK is formulated without chlorinated solvent or lead.

Main Applications



- Open gears on draglines, shovels, excavators, stackers and reclaimers
- Stickshifts
- Circle Rail and rollers
- Heavily loaded, slow moving antifriction bearings
- Bushings
- Open gears in Industrial sector such as cement, waste treatment or steel

Specifications, Approvals & Recommendations

Shell Gadus S4 OGXK is designed to meet the following specifications:

- Bucyrus SD 4713
- P&H 464 Ver 10, 08-16
- CAT Service Bulletin SEBU6250-26 (July 2017)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

| Properties | | | Method | Shell Gadus S4 OGXK |
|-----------------------------|-------|-------------|------------|---------------------|
| NLGI Consistency | | | | 00/000 |
| Colour | | | | Black |
| Soap Type | | | | Al Complex |
| Base Oil (type) | | | | Semi-synthetic |
| Solid Lubricant | | | | Yes |
| Product Kinematic Viscosity | @40°C | cSt minimum | ASTM D2983 | 50 000 |
| Cone Penetration | @25°C | 0.1mm | ASTM D217 | 420 - 455 |

| Properties | | Method | Shell Gadus S4 OGXK |
|---------------------------------|-------------|---|---------------------|
| Four Ball Weld Load | kg | ASTM D2596 | 800 |
| Four Ball Wear Scar | mm maximum | ASTM D2266 | 0.7 |
| Four Ball Load Wear Index (LWI) | kg minimum | ASTM D2596 | 120 |
| Flash Point of base fluid | °C minimum | ASTM D92 | 150 |
| Rust Test | | ASTM D1743 | Pass |
| Copper Strip | 24h @ 100°C | ASTM D4048 | 1b |
| Pumpability, Lincoln Ventmeter | @-50°C | seconds maximum | 30 |
| | | Time to vent from 1800 psi to less than or equal to 600 psi | |

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Gadus S4 OGXK is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Operation Temperatures

General maximum operating temperature +140°C if not restricted by other equipment/application requirements.

• Advice

Advice on applications not covered here may be obtained from your Shell representative.