



Shell Rotella Gas Truck 5W-30

Fully Synthetic Gas Truck Motor Oil

Introducing Shell Rotella Gas Truck full synthetic motor oil, from the makers of Shell Rotella heavy duty engine oil, a leader in diesel engine oil for more than 40 years. Shell Rotella knows truck engines and Shell Rotella Gas Truck full synthetic motor oil provides extreme wear and extreme temperature protection to protect your truck's engine.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- Outperforms conventional motor oil in severe driving conditions
- Protects horsepower
- Provides unsurpassed wear protection
- Protects your truck engine in extreme temperatures and conditions
- Maximum protection for both older and new truck engines
- Helps prevent sludge and other damaging deposits
- Synthetic base oil for added oxidation stability, improved volatility and low-temperature properties
- Helps keep your engine clean

- Shell Rotella Gas Truck 5W-30 can be mixed with other synthetic and mineral oils.

Specifications, Approvals & Recommendations

- API SP-Resource Conserving and all previous categories
- ILSAC GF-6A
- Chrysler MS-6395, MS-13340
- Ford WSS-M2C946-B1
- General Motors GM 6094M
- GM dexos1™ Gen 2 (license D10886IG014)
- For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



- Shell Rotella Gas Truck 5W-30 is recommended for use in all vehicles requiring the use of SAE 5W-30 viscosity grade engine oil under all driving conditions, particularly gasoline pick-ups and SUVs that tend to experience more extreme conditions including driving with heavy load, driving in dusty conditions, stop and go driving, frequent short trips, extreme hot or cold temperatures, and extensive idling.

Typical Physical Characteristics

Properties		Method	Shell Rotella Gas Truck 5W-30
Flash Point	°C	ASTM D92	237
Density	@15°C Kg/m	ASTM D4052	836
Pour Point	°C	ASTM D97	-42
Kinematic Viscosity	@100°C cSt	ASTM D445	11.7

Properties			Method	Shell Rotella Gas Truck 5W-30
Kinematic Viscosity	@40°C	cSt	ASTM D445	66.4

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Rotella Gas Truck 5W-30 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.