

PENNZOIL® HIGH MILEAGE SAE 5W-20 MOTOR OIL

TECHNICAL DATA SHEET



Pennzoil® High Mileage Motor Oil is formulated for engines with 75,000+ miles to help stop leaks from seals and reduce oil consumption in worn engines. It provides proven wear protection, and it's backed by our 10-year, 300,00-mile warranty*. Because at Pennzoil we know, a cleaner, well-sealed engine is better protected and responsive.

*Up to 10 years or 300,000 miles, whichever comes first, if you exclusively use Pennzoil® motor oil, Pennzoil Professional® motor oil, Pennzoil® Gold Synthetic Blend motor oil, Pennzoil® High Mileage motor oil, Pennzoil® High Mileage Full Synthetic motor oil, or Pennzoil® Full Synthetic motor oil. Your engine must have fewer than 125,000 miles and have been manufactured in the past 72 months. To maintain your warranty, change your vehicle's oil and oil filter at least as often as recommended by the vehicle manufacturer. Enrollment required. Keep your receipts. Other conditions apply. See pennzoil.com/warranty to enroll and for full details and terms.

PERFORMANCE, FEATURES & BENEFITS

Pennzoil® High Mileage Motor Oil:

- Recommended for vehicles with 75,000+ miles
- Helps condition engine seals
- Helps prevent sludge and other damaging deposits in high mileage engines
- Provides enhanced protection for worn engine parts
- Helps prevent engine leaks and oil burn-off
- Provides proven wear protection

MAIN APPLICATIONS

Pennzoil® High Mileage SAE 5W-20 is recommended for use in all vehicles requiring the use of SAE 5W-20 viscosity grade engine oils under all driving conditions.

Pennzoil® High Mileage SAE 5W-20 can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Exceeds the requirements of the following industry and OEM specifications:

- ILSAC GF-6A and all previous ILSAC Standards
- API SP-Resource Conserving and all previous categories
- Chrysler MS-6395
- Ford WSS-M2C960-A1

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

PENNZOIL® HIGH MILEAGE SAE 5W-20 MOTOR OIL

TYPICAL PHYSICAL CHARACTERISTICS

Properties		Method	PENNZOIL® HIGH MILEAGE SAE 5W-20 MOTOR OIL
API Service Category			SP-RC
ILSAC			GF-6A
Flash Point	°C	ASTM D92	232
Flash Point	°C	ASTM D93	220
Density	@ 15°C kg/m ³	ASTM D4052	860.5
Viscosity Index		ASTM D2270	151
Kinematic Viscosity	@ 100°C cSt	ASTM D445	8.9
Kinematic Viscosity	@ 40°C cSt	ASTM D445	52.1
CCS Viscosity	@ -30°C cP	ASTM D5293	5 800
MRV Viscosity	@ -35°C cP	ASTM D4684	20 000
Pour Point	°C	ASTM D97	-42

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Safety data sheet available on request. For Health Emergencies or Consumer Information call 1-877-276-7285.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or technical helpdesk.