

# QUAKER STATE HIGH MILEAGE FULL SYN DEXOS 5W-30

FULLY SYNTHETIC MOTOR OIL

TECHNICAL DATA SHEET



## SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

- API SP-Resource Conserving and all previous categories
- ILSAC GF-6A
- Chrysler MS-6395
- Ford WSS-M2C961-A1

- GM dexos1™ Gen 3 (license D335ARDG014)

For a full listing of equipment approvals and recommendations, please consult your local Technical Helpdesk.

To find the right Quaker State® product for your vehicles and equipment, please consult [www.quakerstate.com](http://www.quakerstate.com) to look up the right motor oil recommendation using our oil selector.

## TYPICAL PHYSICAL CHARACTERISTICS

Properties		Method	Quaker State High Mileage Full Syn Dexos 5W-30
Flash Point	°C	ASTM D92	237
Density	@15°C Kg/m <sup>3</sup>	ASTM D4052	836
Pour Point	°C	ASTM D97	-42
Kinematic Viscosity	@100°C cSt	ASTM D445	11.7
Kinematic Viscosity	@40°C cSt	ASTM D445	66.4

These characteristics are typical of current production. While future production will conform to Quaker State's® specification, variations in these characteristics may occur.

## HEALTH, SAFETY & ENVIRONMENT

### Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.