



Shell Helix *HX5 15W-40*

Premium multi-grade motor oil - Helps to remove sludge from dirty engines

Shell Helix HX5 is designed to help provide consistent engine performance. It works hard to help protect against engine sludge and reduce wear. It is suitable for a wide variety of vehicles for everyday driving conditions.

Proud Drivers Choose Shell Helix

Performance, Features & Benefits

- **Active cleansing technology**
Actively locks away harmful performance-robbing deposits.
- **Effective wear protection**
Contains anti-wear agents to help protect against wear.
- **Resistance to oil degradation**
Helps to maintain protection throughout the oil-drain interval.
- **Multi-fuel capability**
Can be used for gasoline and gas engines, and is also suitable and gasoline/ethanol blends.

Main Applications

Shell Helix HX5's premium multigrade formulation helps to provide protection in everyday daily driving conditions. Shell Helix HX5 can be used for gasoline, diesel and gas engines, and it is also suitable for biodiesel and gasoline/ethanol blends.

Specifications, Approvals & Recommendations

- API SL

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: <http://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical help desks.

Typical Physical Characteristics

Properties			Method	Helix HX5 15W-40
Kinematic Viscosity	@40°C	cSt	ASTM D445	105.67
Kinematic Viscosity	@100°C	cSt	ASTM D445	13.92
Viscosity Index			ASTM D2270	133
Density	@15°C	kg/m ³	ASTM D4052	881.1
Flash Point (PMCC)		°C	ASTM D92	235
Pour Point		°C	ASTM D97	-33

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS) which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.