



# Shell Helix *Ultra Professional AT-L 0W-30*

*Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements*

Designed to meet the demanding requirements of particular high-performance engines, including Fiat and those requiring ACEA C2.

## Proud Drivers Choose Shell Helix

### Main Applications

Shell Helix Ultra Professional AT-L 0W-30 for gasoline and diesel engines meets the technically challenging Fiat 9.55535-GS1, 9.55535-DS1 in-house specifications. It is formulated specifically for use in modern Fiat diesel engines using diesel particulate filter technology.

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at <https://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

### Specifications, Approvals & Recommendations

- ACEA C2
- Fiat 9.55535-GS1 - Meets the requirements, Fiat 9.55535-DS1 - Meets the requirements

### Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AT-L 0W-30
Density	@15°C	kg/m <sup>3</sup>	ASTM D4052	837
Kinematic Viscosity	@40°C	cSt	ASTM D445	49.76
Kinematic Viscosity	@100°C	cSt	ASTM D445	9.5
Viscosity Index			ASTM D2270	178
Flash Point		°C	ASTM D92	232
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

#### • Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

#### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.