



Shell Helix *Ultra Professional* AJ-L 5W-30

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

Designed to meet the demanding requirements of particular high-performance engines from Jaguar-Land Rover and those requiring ACEA C1

Proud Drivers Choose Shell Helix

Main Applications

- Shell Helix Ultra Professional AJ-L for diesel engines is approved against the technically challenging in-house technical requirements of the Jaguar Land Rover engine oil specification ST JLR.03.5005.

Specifications, Approvals & Recommendations

- ACEA C1
- Jaguar Land Rover STJLR.03.5005
- Meets requirements of Ford WSS-M2C 934-B

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at <https://lubematch.shell.com>

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AJ-L 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	9.4
Kinematic Viscosity	@40°C	cSt	ASTM D445	63.1
Dynamic Viscosity	@-30°C	cP	ASTM D5293	3 990
Density	@15°C	kg/m ³	ASTM D1298	848.0
Flash Point		°C	ASTM D93	199
Pour Point		°C	ASTM D97	-36
MRV	@-40°C	cP	ASTM D4684	12 800

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on health and safety is available on the appropriate Safety Data Sheet which can be obtained from <https://epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.