



Shell Helix *Taxi* 5W-30

Synthetic Technology Motor Oil - Long term protection against sludge

Shell Helix Taxi 5W-30 is designed particularly for taxi. It helps to keep engines clean and running efficiently by helping to prevent the formation of sludge and engine deposits.

Specifications, Approvals & Recommendations

- API SN PLUS
- API SN/CF

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

Typical Physical Characteristics

Properties			Method	Shell Helix Taxi 5W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	10.4
Kinematic Viscosity	@40°C	cSt	ASTM D445	63.6
Flash Point		°C	ASTM D92	227
Pour Point		°C	ASTM D97	-42
Density	@15°C	kg/m ³	ASTM D4052	857

These characteristics are typical of current production, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shell representative.

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Helpdesk.