

PENNZOIL PLATINUM® EURO SAE 0W-40 FULL SYNTHETIC MOTOR OIL - MADE FROM NATURAL GAS

TECHNICAL DATA SHEET



Pennzoil Platinum® Euro with PurePlus™ Technology is a first of its kind full synthetic motor oil made from natural gas and designed for COMPLETE PROTECTION for top engine performance. Formulated for modern turbocharged engines.

PERFORMANCE, FEATURES & BENEFITS

Pennzoil® is the first motor oil made from natural gas, not crude. Our PurePlus® Technology is the revolutionary process that converts pure natural gas into high quality full synthetic base oil, with fewer impurities than traditional base oils made from crude. Pennzoil Platinum® Full Synthetic motor oil is designed to deliver complete engine protection for top engine performance.

Complete Protection:

CLEANER PISTONS

Helps keep pistons cleaner than required by the toughest industry standard.¹

LOW-SPEED PRE-IGNITION PROTECTION

Protects against damaging low-speed pre-ignition (LSPI) in modern turbocharged direct injection gasoline engines²

PROTECTS HORSEPOWER

Helps protect engines from loss of power.

UNSURPASSED WEAR PROTECTION

No other leading motor oil provides better protection from friction.³

EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES

Provides faster low temperature oil flow and protects in extreme heat.

MAIN APPLICATIONS

Pennzoil Platinum® Euro SAE 0W-40 Full Synthetic Motor Oil can be used in both passenger car gasoline and light duty diesel applications.

Pennzoil Platinum® Euro SAE 0W-40 Full Synthetic Motor Oil meets or exceeds the performance requirements of API SP and ACEA A3/B3, A3/B4.

It is also suitable for use and offers the same protection as SAE 5W-40.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Meets or exceeds the following OEM requirements:

- MB-Approval 229.3/229.5/226.5
- VW 502.00, VW 505.00
- Renault RN 0700, 0710

Exceeds the requirements of the following industry specifications:

- API SP and all previous Categories
- ACEA A3/B3, A3/B4

For a full listing of equipment approvals and recommendations, please consult your local Technical Helpdesk.

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

¹ Based on Sequence IIHF using SAE 0W-40

² Based on ASTM Sequence IX LSPI test run at an independent laboratory

³ Based on Sequence IVA wear test using SAE 5W-30

PENNZOIL PLATINUM® EURO SAE 0W-40 FULL SYNTHETIC MOTOR OIL - MADE FROM NATURAL GAS

TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	PENNZOIL PLATINUM® EURO SAE 0W-40 FULL SYNTHETIC MOTOR OIL
Kinematic Viscosity	@40°C	cSt	ASTM D445	72.2
Kinematic Viscosity	@100°C	cSt	ASTM D445	13.0
Flash Point		°C	ASTM D92	232
Flash Point		°C	ASTM D93	210
Pour Point		°C	ASTM D97	-48
CCS Viscosity	@-35°C	cP	ASTM D5293	5 960
MRV	@-40°C	cP	ASTM D4684	13 200
Density		kg/m ³	ASTM D4052	834
Viscosity Index			ASTM D2270	183

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

Pennzoil Platinum® Euro SAE 0W-40 Full Synthetic Motor Oil with PurePlus™ Technology is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or technical helpdesk.