



# Shell Helix Ultra Professional AO-L 0W-20

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

Designed to meet the demanding requirements of particular high-performance engines from Opel.

## Proud Drivers Choose Shell Helix

### Main Applications

- Shell Helix Ultra Professional AO-L for gasoline and diesel engines is approved against the technically challenging in-house technical requirements of the Opel engine oil specification OV 040 1547- A20.

- Opel/Vauxhall Specification OV 040 1547 - A20 (former OV 040 1547)

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks.

To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at <https://lubematch.shell.com>

### Specifications, Approvals & Recommendations

- ACEA C5
- API SN PLUS

### Typical Physical Characteristics

Properties			Method	Shell Helix Ultra Professional AO-L 0W-20
Density	@15°C	kg/m <sup>3</sup>	ASTM D4052	837
Flash Point		°C	ASTM D92	241
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.6
Kinematic Viscosity	@40°C	cSt	ASTM D445	46.6
Pour Point		°C	IP 15	-51

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Health, Safety & Environment

#### • Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from <https://www.epc.shell.com/>

#### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.