



Shell Rimula R5 LM 10W-40

- Low Emissions
- Maintenance Saving

Synthetic Technology Heavy Duty Diesel Engine Oil

Shell Rimula R5 LM oils feature "Low-SAPS" additive technology. Protective power is energised by synthetic technology that enhances oil performance to deliver responsive protection, resulting in maintenance saving and long oil drain capability.



Performance, Features & Benefits

- **Emissions system capability**
Advanced low-ash formulation helps control blocking of or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.
- **Maintenance saving**
Shell Rimula R5 LM has been formulated to meet the long oil drain requirements of Mercedes-Benz and MAN to allow operators to optimize maintenance scheduling.
- **Improved engine cleanliness**
The advanced formulation delivers good engine cleanliness and protection against piston deposits allowing Shell Rimula R5 LM to ensure engine and component reliability at extended oil drain intervals.

- **European heavy duty engines**

Shell Rimula R5 LM provides protection and performance in modern high power heavy duty diesel engines from leading European engine makers such as Mercedes-Benz and MAN and where oils meeting ACEA E6 are called for.

- **Low emission engine use**

Shell Rimula R5 LM meets the requirements of Mercedes-Benz, MAN and other manufacturers for modern engine applications.

Specifications, Approvals & Recommendations

- MAN M3477, 3271-1
- MB-Approval 228.51
- ACEA E6
- Volvo VDS-3
- Renault RLD-2
- API CI-4

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



Typical Physical Characteristics

Properties			Method	Shell Rimula R5 LM 10W-40
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	81
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	12.8
Dynamic Viscosity	@-25°C	mPa s	ASTM D5293	6600
Viscosity Index			ASTM D2270	158
TBN		mg KOH/g	ASTM D2896	9.7
Sulphated Ash		%	ASTM D874	0.9
Density	@15°C	kg/l	ASTM D4052	0.851
Flash Point (COC)		°C	ASTM D92	248
Pour Point		°C	ASTM D97	-45

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Rimula R5 LM 10W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.